

SAFETY DATA SHEET

PETTIT



Revision Date 25-Jul-2016
Version 1

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Pettit Black Widow Antifouling Racing Finish 1869 Black
Product code 1186906

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Paint
Restrictions on use Read label instructions and SDS

1.3 Details of the supplier of the safety data sheet

Supplier Kop-Coat, Inc. / Pettit Marine Paint
Marine Group
36 Pine Street
Rockaway, NJ 07866
1-800-221-4466

1.4 Emergency telephone number

Emergency telephone number Chemtrec: +1 703-527-3887 ex-USA
Chemtrec: 1-800-424-9300 USA

2. Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 3

2.2 Label elements

Signal Word

Danger

Hazard Statements

Harmful if swallowed

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation

Suspected of causing cancer

May damage fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure

Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell

Rinse mouth

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

2.4 Other information

Not Applicable

Unknown Acute Toxicity 2.483% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients

Substance

Not applicable

Mixture

Chemical Name	CAS-No	Weight %
Cuprous Thiocyanate	1111-67-7	20 - 30
Zinc oxide	1314-13-2	10 - 20
Parachlorobenzotrifluoride	98-56-6	10 - 20
Heavy aromatic naptha	64742-94-5	5 - 10
Xylene	1330-20-7	1 - 5
Zinc pyrithione	13463-41-7	1 - 5
MOLYBDENUM DISULPHIDE	1317-33-5	1 - 5
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Carbon black	1333-86-4	1 - 5
Dibutyl Phthalate	84-74-2	1 - 5
ALIPHATIC NAPHTHA	64742-89-8	1 - 5
Naphthalene	91-20-3	1 - 5
Ethylbenzene	100-41-4	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1 Description of first-aid measures

General advice

For further assistance, contact your local Poison Control Center.

Eye contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Call a poison control center or doctor for treatment advice.

Skin contact

Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a poison control center or doctor for treatment advice.

Inhalation

Move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a poison control center or doctor for treatment advice.

Ingestion

Rinse mouth. Do NOT induce vomiting. Call a physician or poison control center immediately. If a person vomits when lying on his back, place him in the recovery position.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

There is no specific antidote for effects from overexposure to this material. Treat symptomatically.

5. Fire-Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media

Foam. Carbon dioxide (CO₂). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers

that are exposed to the heat from a fire.

Unsuitable Extinguishing Media Water may be unsuitable for extinguishing fires.

5.2 Special hazards arising from the substance or mixture

Special Hazard

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to release of irritating gases and vapors

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

Explosion Data

Sensitivity to Mechanical Impact Not sensitive.

Sensitivity to Static Discharge Yes.

5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

6.2 Environmental precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

6.3 Methods and materials for containment and cleaning up

Methods for Containment Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Ground and bond containers when transferring material. Take precautionary measures against static discharges.

7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking.

Hygiene measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.

Materials to Avoid No materials to be especially mentioned.

8. Exposure controls/personal protection

8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWA/EV
Cuprous Thiocyanate 1111-67-7	TWA: 1 mg/m ³ Cu dust and mist	-				
Zinc oxide 1314-13-2	STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 2 mg/m ³ STEL: 10 mg/m ³	TWA: 2 mg/m ³ STEL: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 2 mg/m ³ STEL: 10 mg/m ³
Parachlorobenzotrifluoride 98-56-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm STEL: 150 ppm
MOLYBDENUM DISULPHIDE 1317-33-5	TWA: 10 mg/m ³ Mo inhalable fraction TWA: 3 mg/m ³ Mo respirable fraction	TWA: 15 mg/m ³ total dust	TWA: 3 mg/m ³ TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³
Dibutyl Phthalate 84-74-2	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³ Adverse reproductive effect	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³	TWA: 10 ppm STEL: 15 ppm Skin	TWA: 10 ppm TWA: 52 mg/m ³ STEL: 15 ppm STEL: 79 mg/m ³ Skin	TWA: 10 ppm TWA: 52 mg/m ³ STEL: 15 ppm STEL: 79 mg/m ³	TWA: 10 ppm STEL: 15 ppm Skin
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³	TWA: 20 ppm

8.2 Appropriate engineering controls

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

8.3 Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields. If splashes are likely to occur, wear.. Tightly fitting safety goggles. Face-shield.

Skin and body protection Solvent-resistant gloves. Nitrile rubber. Neoprene gloves. Impervious butyl rubber gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove

and wash contaminated clothing before re-use. Long sleeved clothing. Protective shoes or boots.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

See section 7 for more information

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No information available
Color	Black
Odor	Hydrocarbon-like
Odor Threshold	No information available

Property	Values	Remarks • Methods
pH		No information available
Melting/freezing point		No information available
Boiling point/boiling range		No information available
Flash Point	43 °C / 109 °F	
Evaporation rate		No information available
Flammability (solid, gas)		No information available
Flammability Limits in Air		
upper flammability limit		No information available
lower flammability limit		No information available
Vapor pressure		No information available
Vapor density		No information available
Specific Gravity		No information available
Water solubility		No information available
Solubility in other solvents		No information available
Partition coefficient		No information available
Autoignition temperature		No information available
Decomposition temperature		No information available
Viscosity, kinematic	> 22 mm ² /s	
Viscosity, dynamic		No information available
Explosive properties		No information available
Oxidizing Properties		No information available

9.2 Other information

Volatile organic compounds (VOC) content	302 g/L
Density	13.55 lb/gal

10. Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use

10.2 Chemical stability

Stable under recommended storage conditions

10.3 Possibility of hazardous reactions

None under normal processing.

10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

10.5 Incompatible Materials

No materials to be especially mentioned.

10.6 Hazardous Decomposition Products

None under normal use conditions. Thermal decomposition can lead to release of irritating gases and vapors.

11. Toxicological information

11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity 2.483% of the mixture consists of ingredient(s) of unknown toxicity

Oral LD50	1,473.00 mg/kg
Dermal LD50	3,390.00 mg/kg
LC50 (Dust/Mist)	4.40 mg/l
LC50 (Vapor)	131.00 mg/l

Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Zinc oxide 1314-13-2	5000 mg/kg (Rat)	-	-
Parachlorobenzotrifluoride 98-56-6	> 6800 mg/kg (Rat)	> 2700 mg/kg (Rabbit)	= 33 mg/L (Rat) 4 h
Heavy aromatic naptha 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
Xylene 1330-20-7	3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Zinc pyrithione 13463-41-7	269 mg/kg (rat)	> 2000 mg/kg (rabbit)	= 1.03 mg/L (Rat) 4 h
MOLYBDENUM DISULPHIDE 1317-33-5	-	-	> 2820 mg/m ³ (Rat) 4 h
1,2,4-Trimethylbenzene 95-63-6	3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Dibutyl Phthalate 84-74-2	6300 mg/kg (Rat)	> 20 mL/kg (Rabbit)	> 15.68 mg/L (Rat) 4 h
ALIPHATIC NAPHTHA 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
Naphthalene 91-20-3	1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h
Ethylbenzene 100-41-4	3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

11.2 Information on toxicological effects

Skin corrosion/irritation

Product Information

- No information available

Component Information

- No information available

Serious eye damage/eye irritation

Product Information

- No information available

Component Information

- No information available

Respiratory or skin sensitizationProduct Information

- No information available

Component Information

- No information available

Germ cell mutagenicityProduct Information

- No information available

Component Information

- No information available

CarcinogenicityProduct Information

- The table below indicates whether each agency has listed any ingredient as a carcinogen

Component Information

- Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon black 1333-86-4	-	Group 2B	-	
Naphthalene 91-20-3	-	Group 2B	Reasonably Anticipated	
Ethylbenzene 100-41-4	-	Group 2B	-	

Reproductive toxicityProduct Information

- No information available

Component Information

- No information available

STOT - single exposure

No information available

STOT - repeated exposure

- No information available

Other adverse effectsProduct Information

- No information available

Component Information

- No information available

Aspiration hazardProduct Information

- No information available

Component Information

- No information available

12. Ecological information

12.1 Toxicity**Ecotoxicity**

No information available

5.20149 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Ecotoxicity effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Parachlorobenzotrifluoride 98-56-6	-	-	EC50: 48 h Daphnia magna 3.68 mg/L
Heavy aromatic naptha 64742-94-5	-	LC50: 96 h Pimephales promelas 19 mg/L static LC50: 96 h Oncorhynchus mykiss 2.34 mg/L LC50: 96 h Lepomis macrochirus 1740 mg/L static LC50: 96 h Pimephales promelas 45 mg/L flow-through LC50: 96 h Pimephales promelas 41 mg/L	EC50: 48 h Daphnia magna 0.95 mg/L
Xylene 1330-20-7	-	LC50: 96 h Pimephales promelas 23.53 - 29.97 mg/L static LC50: 96 h Cyprinus carpio 780 mg/L semi-static LC50: 96 h Cyprinus carpio 780 mg/L LC50: 96 h Poecilia reticulata 30.26 - 40.75 mg/L static LC50: 96 h Pimephales promelas 13.4 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L static LC50: 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L LC50: 96 h Lepomis macrochirus 13.1 - 16.5 mg/L flow-through LC50: 96 h Lepomis macrochirus 19 mg/L LC50: 96 h Lepomis macrochirus 7.711 - 9.591 mg/L static	EC50: 48 h water flea 3.82 mg/L LC50: 48 h Gammarus lacustris 0.6 mg/L
1,2,4-Trimethylbenzene 95-63-6	-	LC50: 96 h Pimephales promelas 7.19 - 8.28 mg/L flow-through	EC50: 48 h Daphnia magna 6.14 mg/L
Dibutyl Phthalate 84-74-2	EC50: 72 h Desmodesmus subspicatus 1.2 mg/L EC50: 96 h Pseudokirchneriella subcapitata 0.4 mg/L static	LC50: 96 h Pimephales promelas 0.71 - 1.2 mg/L flow-through LC50: 96 h Pimephales promelas 0.31 - 5.45 mg/L static LC50: 96 h Oncorhynchus mykiss 1.24 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 1.24 - 5.3 mg/L static LC50: 96 h Lepomis macrochirus 1.38 - 1.74 mg/L flow-through LC50: 96 h Lepomis macrochirus 0.42 - 1.28 mg/L static	EC50: 48 h Daphnia magna 2.99 mg/L Static EC50: 48 h Daphnia magna 3.4 mg/L
ALIPHATIC NAPHTHA 64742-89-8	EC50: 72 h Pseudokirchneriella subcapitata 4700 mg/L	-	-
Naphthalene 91-20-3	-	LC50: 96 h Pimephales promelas 5.74 - 6.44 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 1.6 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 0.91 - 2.82 mg/L static LC50: 96 h Pimephales promelas 1.99 mg/L static LC50: 96 h Lepomis macrochirus 31.0265 mg/L static	LC50: 48 h Daphnia magna 2.16 mg/L EC50: 48 h Daphnia magna 1.96 mg/L Flow through EC50: 48 h Daphnia magna 1.09 - 3.4 mg/L Static
Ethylbenzene 100-41-4	EC50: 72 h Pseudokirchneriella subcapitata 4.6 mg/L EC50: 96 h Pseudokirchneriella subcapitata 438 mg/L EC50: 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L static EC50: 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L static	LC50: 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L static LC50: 96 h Oncorhynchus mykiss 4.2 mg/L semi-static LC50: 96 h Pimephales promelas 7.55 - 11 mg/L flow-through LC50: 96 h Lepomis macrochirus 32 mg/L static LC50: 96 h Pimephales promelas 9.1 - 15.6 mg/L static LC50: 96 h Poecilia reticulata 9.6 mg/L static	EC50: 48 h Daphnia magna 1.8 - 2.4 mg/L

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
Parachlorobenzotrifluoride 98-56-6	3.7
Heavy aromatic naptha 64742-94-5	6.1
Xylene 1330-20-7	3.15
1,2,4-Trimethylbenzene 95-63-6	3.63
Dibutyl Phthalate 84-74-2	5.38
Naphthalene 91-20-3	3.3
Ethylbenzene 100-41-4	3.118

12.4 Mobility in soil

No information available.

12.5 Other adverse effects

No information available

13. Disposal Considerations**13.1 Waste treatment methods**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. Transport Information**Note** DOT Ground - "Non-bulk shipments may be non-regulated per 49CFR 173.150(f)(2)"**DOT** Not regulated (If shipped in NON BULK packaging by ground transport)**MEX** no data available**IMDG**

Proper shipping name	UN1263, Paint, 3, III
Marine pollutant	Marine pollutant

IATA

Proper shipping name	UN1263, Paint, 3, III
-----------------------------	-----------------------

15. Regulatory information**15.1 International Inventories**

TSCA	Complies
DSL	-
EINECS/ELINCS	-
ENCS	-
IECSC	-
KECL	-
PICCS	-
AICS	-
NZIoC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

15.2 U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Cuprous Thiocyanate 1111-67-7	1.0
Zinc oxide 1314-13-2	1.0
Xylene 1330-20-7	1.0
Zinc pyrithione 13463-41-7	1.0
1,2,4-Trimethylbenzene 95-63-6	1.0
Dibutyl Phthalate 84-74-2	1.0
Naphthalene 91-20-3	0.1
Ethylbenzene 100-41-4	0.1

15.3 Pesticide Information

U.S. EPA Pesticide Information

EPA Pesticide Registration Number 60061-116

EPA Statement

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

EPA Pesticide Label

DANGER. Corrosive. Causes skin burns and moderate eye irritation. Harmful if inhaled or swallowed.

15.4 U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Carbon black - 1333-86-4	Carcinogen
Dibutyl Phthalate - 84-74-2	Developmental Female Reproductive Male Reproductive
Naphthalene - 91-20-3	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
N-METHYL-2-PYRROLIDONE - 872-50-4	Developmental
Crystalline silica (quartz) - 14808-60-7	Carcinogen
Toluene - 108-88-3	Developmental Female Reproductive
CUMENE - 98-82-8	Carcinogen

Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Cadmium - 7440-43-9	Carcinogen Developmental Male Reproductive
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

16. Other information

NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2*	Flammability 2	Physical Hazard 0	Personal protection X

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

Ceiling (C)

DOT (Department of Transportation)

EPA (Environmental Protection Agency)

IARC (International Agency for Research on Cancer)

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG)

NIOSH (National Institute for Occupational Safety and Health)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL (Permissible Exposure Limit)

Reportable Quantity (RQ)

Skin designation (S*)

STEL (Short Term Exposure Limit)

TLV® (Threshold Limit Value)

TWA (time-weighted average)

Revision Date 25-Jul-2016**Revision Note**
No information available**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet