

Valve

Product Numbers

PV-70-10 and PV 70-12

Description

PE double O-ring infusion valve. Available in 10 mm and 12 mm o/d. Maximum use temperature 100°C (212°F).



Technical Data

| Part Number | Material | Outside Dia. | | Max Temp | |
|-------------|----------|--------------|-------|----------|-------|
| PV-70-10 | PE | 10 mm | 0.39" | 100°C | 212°F |
| PV-70-12 | PE | 12 mm | 0.47" | 100°C | 212°F |

Resin Inlet

Product Number

PV-72-16

Description

Infusion inlet block. 16 mm diameter. Self-seals with Resin Inlet Connector (PV-73) and Omega Resin Feed (PV-64). Can be used up to 100°C (212°F).



| Part Number | Material | Interior Dia. | | Height | | Max Temp | |
|-------------|----------|---------------|-------|--------|-------|----------|-------|
| PV-72-16 | PE | 16 mm | 0.63" | 35 mm | 1.38" | 100°C | 212°F |



Resin Inlet Connector

Product Numbers

PV-73-12

Description

PE, L connector for inlet block. Can be used up to 100°C (212°F).



Technical Data

| Part Number | Material | Outside Dia. | | Shape | Max Temp | |
|-------------|----------|--------------|-------|-------|----------|-------|
| PV-73-12 | PE | 12 mm | 0.47" | L | 100°C | 212°F |

T Connector

Product Numbers

PV-76-10 and PV-76-12

Description

PE, T connectors for resin infusion. Available in 10 mm and 12 mm. Can be used up to 100°C (212°F).



| Part Number | Material | Outside Dia. | | Shape | Max Temp | |
|-------------|----------|--------------|-------|-------|----------|-------|
| PV-76-10 | PE | 10 mm | 0.39" | T | 100°C | 212°F |
| PV-76-12 | PE | 12 mm | 0.47" | T | 100°C | 212°F |



L Connector

Product Number

PV-77-10

Description

PE, L connector for resin infusion. Available in 10 mm. Can be used up to 100°C (212°F).



| Part Number | Material | Outside Dia. | | Shape | Max Temp | |
|-------------|----------|--------------|-------|-------|----------|-------|
| PV-77-10 | PE | 10 mm | 0.39" | L | 100°C | 212°F |

