

## Technical Data Sheet

### WHITE GELCOAT (NO WAX)

#### DESCRIPTION

MMS™ Premium Marine Gel Coat – White, No Wax is a high-performance, marine-grade gel coat designed for professional repair, refinishing, and OEM applications. This is a non-wax formula. It is suitable for both above- and below-waterline use on fiberglass, composites, and other marine surfaces. The gel coat features a smooth, high-gloss finish and excellent UV stability when properly top coated. It is additive-friendly and compatible with spray, brush, or roll application methods. Appropriate additives are Duratec high gloss, sanding aid and patch booster.

<b>Appearance</b>	White
<b>Viscosity LV4@6</b>	15,000-18,000 cps
<b>Viscosity LV4@60</b>	2,200-3,200 cps
<b>Thix</b>	5-7
<b>Gel Time 100g mass MEKP-925 1.5%</b>	14-18 minutes
<b>Weight Per Gallon</b>	10.3-10.8
<b>Hide</b>	18-22 mils
<b>Barcol Hardness</b>	35
<b>Thin Film</b>	60 minutes
<b>VOC (Styrene)</b>	36-40%

\* This material is for professional use only. Use adequate ventilation and protection from eye and skin exposure. Any information supplied with this material is given in good faith and must be verified by the end user, as is the sustainability of the material for their application. The warranty of this material shall be limited to the replacement of defective material.